



Endurogrip on Enduroplank™

Installation and Maintenance

1800REPLAS | sales@replas.com.au

Installation:

Standard installation methods for Enduroplank™ should be followed as per Replas recommendations. The boards must be handled with extra care to avoid damaging the coating prior to job completion, placing sharp tools or objects on the deck surface during construction should be avoided.

When cutting the board, saw blade life may be extended by ensuring the teeth of the blade cut from the underside (non-coated) of the board.

Suitable gloves must be worn by the installer to avoid injury from the abrasive surface.

Maintenance:

After construction, the entire surface should be cleaned of plastic swarf and other debris, this can be done with an air blower, broom, or hose.

On-going maintenance to ensure the highest level of anti-slip requires regular inspection of the surface for damage and contaminants, it is recommended this be done twice annually. The inspection frequency may need to be higher in areas prone to plant debris, mud or other contaminants.

Cleaning of surface contaminants should take place immediately to avoid a slip hazard and possible damage to the coating.

Cleaning of the surface:

The recommended method of cleaning is by the use of a soft brush and mild detergent.

The use of a pressure cleaner is not recommended and damage sustained from the use of a pressure washer may void the warranty.

Due to the variations in cleaning products and equipment, it is always recommended that any cleaning method be assessed in an inconspicuous area of the deck prior to full scale application.